

Prehung Steel Door Units

Premdor Entry Systems are available in any of the configurations shown here.

D
PE 106 - 515



Door

SD/DS
PE 300 - 724B



Sidelite/Door (shown)
or Door/Sidelite

SDS
PE 135 - 724A



Sidelite/Door/
Sidelite

DD
PE 120 - 430



Double Door

SDDS
PE 129 - 920B



Double Door/
Double Sidelite

OUTSWING



Left hand outswing shown

Door handings are always determined from the outside of the building.

INSWING



Right hand inswing shown

If you require increased air circulation through your front entry, consider adding a venting sidelite to your unit. A traditional inswing door combined with an outswing sidelite complete with crank arm, camlock closers and an interior removable screen offers the ultimate in controlled, insect free ventilation.

Not available with 12 sidelites or stain grade jamb.

Venting sidelites



PE 105 - 620A


Direct Glazing



Optional steel kick panel shown

If your entry requires special sizing consider replacing custom sized sidelites or doors with direct glazed sidelites and/or transoms. Using twin sealed glass units installed directly into the prehung frame saves time and money compared to the cost and delay of factory ordered, custom built sidelites or doors.

Available in a wide variety of glass or grid options and with or without steel kick panels.



Venting Sidelite (SD) shown

WeatherLock Garden Doors

WeatherLock Garden Doors are designed for easy replacement of 5 and 6 sliding patio doors (rough openings of 60 x 80 and 72 x 80) or full height (R/O 81-1/2) for new construction.

- Cam lock closers seal out the weather and improve security
- High quality hardware is used on every WeatherLock Door
- Primed #1 jamb and components
- Thermally broken all aluminum sill
- Removable screen

GLASS OPTIONS



Brass
Internal Grids



White
External Grid



White
Internal Grid



Mini Blind



Camlock Closers
(2 per door)



High Quality
Mohair Sweep



Brass Plated
Security Hinges
(Non-Removable Pin)



A unique feature of our Garden Door is a screened ventilation door. Simply turn the crank handle to extend or retract the door. Hardware can be detached to allow full swing out operation.