

1. **Premium Polyurethane Foam Core**
 - Excellent insulating value
 - 5 times better insulation than wood
 - R-15
2. **Polyester Primed Surface**
 - Polyester primer paint
 - Durable, easy to clean
 - Paintable to match any decor
3. **Rigid Galvanized Steel Skin**
 - 24 gauge galvanized steel
 - Strong and secure
 - Rust-free performance
 - Building code approved
4. **Embossed and Flush Designs**
 - Select the right look for your door from a wide range of patterns
 - Paintable surface and edges
5. **Solid Lock Block**
 - Double drilled for easy lockset and deadbolt installation
6. **Folded Top and Bottom Edges**
 - Clean, crisp straight edges
7. **Engineered Stiles and Rails**
 - Inter-locking steel skin
 - This engineered connection prevents stile and skin separation, ensuring precise door thickness from top to bottom.
 - Excellent thermal break
 - Interlocking corners for rigid stability



Door styles

Most doors are available in standard 79 heights, 29-3/4, 31-3/4, 33-3/4 and 35-3/4 widths. Custom sizes available by special order.

105 23 x 37 Round Top Cut Out	106 23 x 37 Cut Out	109 23 x 65 Round Top	120 21 x 65 Cut Out	2 x 129 9 x 37 Cut Out	135 Sunburst Cut Out	136 9 Panel Arch Top Cut Out
136 6 Panel 79	200 12 Panel Square Top Cut Out	300 9 x 37 Round Top	304 Oval Cut Out	410 Mini Oval Cut Out	404 S Top Cut Out	404 23 x 49 Cut Out
450 9 x 49 Cut Out	8P 8 Panel Parliament	8P 8 Panel	Flush 79 Flush 79	4 Panel New England 4 Panel New England	Flush 83 & 95 Flush 83 & 95	6 Panel 83 & 95 6 Panel 83 & 95



PREMDOR
Entry Systems

FACTORY APPLIED FINISHES

PAINTED



STAINED



PAINT: Paint finishes can be applied to steel and fibreglass doors
STAIN: Stain finishes can be applied to fibreglass doors.

*Actual pre-finished door colour may not be exactly as shown

Prem Helpline: **1-800-663-DOOR (1-800-663-3667)**
9 a.m. to 9 p.m. Monday through Saturday,
10 a.m. to 4 p.m. Sunday, EST
e-mail: help@premdor.com
Web site: www.masonite.com

Distributed By: